




CONTROLS PRESET POSITION, PAN/TILT, ZOOM/FOCUS, DIGITAL CAMERA FUNCTIONS AND RECEIVER/HOUSING.

Panasonic introduces the WV-CU161 system controller. When combined with the WV-CS850 Series new Super Dynamic II Colour Dome Camera, the WV-CU161 enables remote control of various functions for the WV-CS850 Series. The WV-CS850 Series is a highly advanced and unitized device. Features include 64 preset positions, 300 degree/sec. panning, 360 degree endless panning, 22X zoom and 10X electronic zoom lens. Other features include Patrol Learn Function, colour or selectable B/W mode and progressive digital functions. WV-CU161 allows for direct and accurate control of the WV-CS850 Series with user-friendly operation. The WV-CU161 can control WV-CS850 Series up to 1,200 m using RG-6/U (5C-2V). With an Alarm input/output function and Alarm reset input/output function, WV-CU161 can transfer an alarm signal to an external equipment, such as motion detector. The WV-CU161 is an integral part of any high performance surveillance system.


Key Features

- Preset Control (64 positions function, focus, zoom ratio, rotation mode, etc.)
- Lens Control (zoom ratio, focus, iris)
- Pan/Tilt Control (manual pan, manual tilt, auto-pan)
- Receiver Control (wiper, defroster, AUX 1-2)
- Camera Control (home position, camera setting, patrol function)
- Preset Control interlocked to alarm signal
- Built-in Alarm Recover Input/Reset Output
- Built-in RS-485 Terminal
- Joystick
- Preset Data (up/download function, maximum 8 cameras)



An Example of Setup Menu

MAJOR OPERATING CONTROLS



SPECIFICATIONS PAL


Power Source	220 - 240 V AC50 Hz
Power Consumption	7 W
Camera Input	Composite Video Signal 1.0 V [p-p] / 75Ω
Alarm input	Max. 4 input
Video Output	Composite Video Signal 1.0 V [p-p] / 75Ω, multiplexed video and control data
Alarm Output	Open Collector Output 16 V DC, 100 mA max.
RS-485 Terminal	RS-485, full (4 line) or half (2 line) switchable
Lens Control	Zoom: Tele / Wide (Electronic zoom WV-CS850 Series only) Focus: Near / Far / Auto Focus Iris: Open / Close / Reset
Pan / Tilt Control	Manual: Selectable at variable speed control Auto Pan: On / Off
Housing Control	Wiper: On / Off Defroster: On / Off AUX 1.2: On / Off
Camera Control	Position Select: Selectable 1 to 64 (max.) Home Position: Possible Camera Setup: Possible Patrol Learn Function: Available on WV-CS850 Series only B/W, Colour Mode: Selectable on WV-CS850 Series only
Memory	Camera Preset Data Upload / Download (Max. 8 cameras)
Alarm	Alarm Buzzer: On / Off Alarm Display: On / Off Auto Reset / Manual Reset: Possible Alarm Suspend: Possible
Ambient Operating Temperature	-10°C - +50°C
Ambient Operating Humidity	Less than 90%
Dimensions	330 (W) x 74.5 (H) x 221 (D) mm
Weights	2.4 kg

Specifications are subject to change without notice.
Dimensions and weight are approximate.
This product may be subject to export control regulations.


DISTRIBUTED BY:

SYSTEM CONFIGURATION


Basic Connection



Application Connection with the Passive Video Switcher



APPEARANCE



OPTIONAL ACCESSORIES

Super Dynamic II Dome Camera WV-CS850 Series

- 64-position presettable
- Digital Motion Detector
- Electronic Sensitivity Up
- Automatic Focus
- Max. 300 / Second Panning
- Privacy Zone Masking
- Patrol Learn Function
- B/W, Colour Mode selectable
- 22x Zoom / 10x Electronic Zoom



Receiver
WV-RC100 / WV-RC150

Rack Mount Angle
WV-Q62

Panasonic

Panasonic is the brandname of Matsushita Electric.
Printed in Japan
(2N-662)